

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 365 366 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

26.11.2003 Bulletin 2003/48

(51) Int Cl.7: G07F 17/32

(21) Application number: 03011455.7

(22) Date of filing: 20.05.2003

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR

Designated Extension States:

AL LT LV MK

(30) Priority: 21.05.2002 JP 2002146803

(71) Applicant: Aruze Co., Ltd.

Tokyo 135-0063 (JP)

(72) Inventor: Okada, Kazuo, c/o Aruze Co., Ltd.
Koutou-ku, Tokyo, 135-0063 (JP)


(74) Representative:

TER MEER STEINMEISTER & PARTNER GbR
Patentanwälte,
Mauerkircherstrasse 45
81679 München (DE)

(54) Gaming apparatus

(57) A gaming apparatus control part is provided with an external output control circuit, configured in such a manner that gaming information can be output and gaming data sent from each gaming machine is collected in a management server in order to solve the issue that internal winning attraction is limited to each gaming apparatus and a player concentrates only on the gaming apparatus to which he is playing. The management server comprises a link attraction lottery table to determine attraction mode based on sent gaming information and link attraction transmission unit lottery table to determine a destination gaming apparatus of link attraction, determines a link attraction and attraction transmission destination, and sends an attraction data with a pre-determined timing on the condition that internal winning data is sent from a gaming apparatus.

Fig. 1



Description

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The present invention relates to a symbol combination gaming apparatus such as a slot machine and a pachinko comprising a varying display means to varyingly display various symbols and a function to control the varying display to provide a player with a benefit depending on the result, and a gaming apparatus system using a hall management computer to manage a gaming history.

Related art

RELATED ART

[0002] A slot machine can be cited as typical example of this kind of gaming apparatus. The slot machine has a plurality of rotating reels, in which a plurality of symbols are provided on the circumference thereof. A prize is defined as a prize state where a combination of symbols when each rotating reel stopped becomes same as a predetermined stopping state, i.e., the same symbols line up on a pay line specified by the player, it is so configured that a predetermined amount of coin or giveaway is paid out. In general, types of contingency are often added to obtain this prize. The gaming apparatus is characterized by contingency that a player cannot totally control the result of a game with his skill.

[0003] In order to realize the "contingency", various methods have been adopted. Recently, a control method called "pre-judgment" to control reels to stop depending on the result of the lottery after carrying out a prize lottery through a software with a microcomputer is adopted in a slot machine. For example, a slot machine described in Japanese Patent No. 1991-72313 is a so called pachi-slot gaming machine with stop buttons, comprising a random number sampling means to sample a random number based on the start lever operation by a player, and a prize probability table separated into each random number range of "big hit", "mid hit" and "small hit" depending on the largeness of a prize pattern. Then it judges that the prize pattern wins to establish a hit (winning) flag of the relevant prize pattern if a sampled random number falls on the winning section of the prize probability table. These winning flags include the winning flag of the prize pattern called "small prize pattern" in which about ten pieces of coins are discharged by matching predetermined symbols (eg., "bell" or "cherry") on an effective prize line, and the one called a "bonus pattern" a state to generate a prize more easily than normal gaming states during a predetermined times of gaming, to payout about 100 to 400 pieces of coins by predetermined symbols matched (e.g., "7" or "BAR" symbol).

[0004] The state of winning flag established is the one called "internal winning" in general. A related prize pattern is just allowed to be lined up on the prize line and no prize is generated actually. In order to generate a prize, rotating prize symbols shall be controlled with a timing to stop them on a prize line (normally, within four frames) This operation is called "frame press". If this operation timing is bad, prize is not generated though an internal winning is generated. This state is called "missed winning"

[0005] This missed winning, in a large sense, may be caused by the missed frame press. The causes include some patterns. First, an aimed symbol has been determined, however, a player can not recognize varying symbols and stops reels at a rough estimate to fail. Second, there are plural prize patterns that may win within the current game, and a player does not know which symbol to be stopped and fail.

[0006] In the former case, a player can improve the accuracy in some measure if he is skilled in the frame press technique. However, in the latter case, a player must understand the internal winning state which can not be seen from outside. However much a player skilled in the frame press, it is not possible to improve the accuracy of the frame press.

[0007] On the contrary, if an internal winning pattern is informed, it is possible to realize gaming states such as a bonus gaming in which a lot of coins are obtained even in the ordinary gaming state. There are gaming apparatuses with a function called "Assist Time (AT)", function that reduces missed winning and pays out a larger amount of coins than normal gaming, by taking advantage of gaming property specific to pachinko-slots, when predetermined conditions are met, by reporting an internal winning, further, a type of the internal winning pattern during a predetermined period. A state during AT falls into the category of the "gaming state" mentioned below. But it is possible to specify to practically pay out coins comparable to that of the bonus gaming.

[0008] There is also a function "Super Time (ST)" that changes the amount of coins paid out depending on whether winning of "internal winning state" is supported or not. When a rotating reel is controlled to stop by the operation of a stop button by a player, plural "stop tables" for determining the number of frames slipped from the pattern position at which the stop operation has been carried out are provided, a stop table is selected by random number lottery every times when a winning pattern is internal selected. The stop control of the function is composed that no winning is generated, even if buttons are so pressed in the timing of the frame press that the reel can stop on the effective winning line, unless a stop operation is carried out in order of the stop operation specified in the stop table. The function of ST realizes a large number of coins comparable to the bonus gaming as "AT function" mentioned above by assigning an "announced" state of the type of the stop table selected and an "unannounced" state of that to the selected stop

"table.

[0009] As shown above, a gaming state in which a large number of coins can be obtained other than the bonus gaming is called "particular game" in the present invention. Including specific game and bonus gaming state in which a large number of coin payout is carried out is called "special game"

[0010] A player plays games hoping these special games occur. Regardless to say, the probability of a special game changes depending on the business policy of a parlor. For example, a parlor offers a large number of coins to players in a so called service day with a higher probability of special game, or makes profits by reducing payout in a day of profit collection.. Further, in the same parlor and time, some gaming apparatuses easily offer special games and others not. In general, in present-day pachinko parlors (parlors), the operation data of gaming apparatuses are collected in real time and states of gaming apparatuses are monitored. They gain appropriate business profits by aggregating the gaming data outputted by gaming apparatuses with a parlor management computer and adjusting probability of special games based on the data analysis.

[0011] Specifically, probability of special games is changed by changing the payout rate occurrence by changing the setting switch to adjust the probability of occurrence of special games built in each gaming apparatus.. In general, a player can not recognize the setting state. However, a player can recognize the probability of occurrence of special games if he can know the number of generated special games and the game number until then even if he can not confirm the setting of a gaming apparatus. Players have strongly requested construction of a system to confirm the past gaming history of gaming apparatuses

[0012] In this situation, a system where a gaming information display unit to display current gaming record of a gaming apparatus by utilizing a gaming apparatus data collection system of a parlor is located on the way from a gaming apparatus to a parlor management computer and a player can confirm the display for making decision in selecting a gaming apparatus, has been proposed. The information display device is installed at the upper side of each gaming apparatus to offer various gaming apparatus information to players.

[0013] On the other hand, gaming apparatuses to offer various attractions using liquid crystal displays and stereo speakers with attraction control board improved significantly have been proposed. Attractions include information of an establishment of an internal winning flag, a suggestion of an appropriate operation method, execution of prize attraction, attraction during a bonus, etc. Attractions are controlled depending on the gaming states. In these attraction controls, players are greatly interested in an attraction to inform the internal winning of bonus pattern mentioned above, an attraction to inform an internal winning pattern established during AT gaming, an attraction to inform an appropriate stop pro-

cedure during ST gaming and so on, and the above attractions are essential parts of representations installed in a pachi-slot gaming machine.

[0014] However, at present, though various attractions are offered, gaming control information that is a basis to determine the content of attraction is limited to a single gaming apparatus and variation of attraction is likely to be confined.

[0015] Represented units have been confined to a single gaming apparatus. Players are likely to focus on a gaming apparatus that he is using. A lot of gaming apparatuses located in a parlor are not utilized effectively on the attraction basis.

15 SUMMARY OF THE INVENTION

[0016] An object of the present invention is to provide a gaming system with a new gaming property by excluding limitations caused by attraction controls of gaming apparatuses on a single unit basis and utilizing many gaming apparatuses located in a parlor reciprocally.

[0017] A gaming system according to the present invention comprises a gaming apparatus for executing lottery of a prize pattern based on a predetermined input signal and offering profits to a player when a winning is generated, a control and management means for storing gaming information sent from the plural gaming apparatuses, a display means for controlling the display of an attraction based on the gaming information, in which the control and management means is provided with a link attraction determination means to determine an execution of a link attraction referring to the gaming information.

[0018] The present invention relates to a slot machine with a stop button for determining whether a prize is generated, a so called pachi-slot gaming machine as a gaming apparatus to generate various gaming information, that judges winning or non-winning of an internal winning pattern determined by the random number lottery process and whether rotating reels are operated with an appropriate timing, outwardly send the bonus winning information generated by gaming operation of a player through an external output control circuit

[0019] The gaming information sent is gathered in a management server as a parlor management computer through LAN constructed in a parlor. The management server determines a link attraction carried out by a link attraction determination means and sends an attraction data.

[0020] The link attraction determination means further comprises a link attraction mode determination means to determine an attraction mode of a link attraction, monitors whether gaming information sent from each gaming apparatus includes bonus internal winning information, and decides a link attraction mode if bonus internal winning information is included with a link attraction mode lottery table.

[0021] Further, a gaming system of a second embod-

iment according to the present invention comprises a gaming apparatus for executing lottery of a prize pattern based on a predetermined input signal and offering profits to a player when a prize is generated, a gaming information display device for receiving gaming information sent from the gaming apparatuses and displaying the gaming information, a control and management means for storing gaming information sent from the plural gaming apparatuses, in which the control and management means is provided with a link attraction determination means to determine an execution of a link attraction referring to the gaming information, and a link attraction transmission means to send the link attraction determined by the link attraction determination means to the gaming information display device.

[0022] Link attraction data determined by the link attraction mode determination means is sent to a gaming information display device located corresponding to each gaming apparatus to carry out attraction control. In general, since a gaming information display device is located above a gaming apparatus, other players can recognize the attraction mode carried out. It is configured in such a manner players can recognize gaming apparatuses in which an attraction is being carried out.

[0023] Still further, a third embodiment according to the present invention comprises a lamp display part constituted of plural lamps and said link attraction is displayed with the mode of lighting of said lamp display part.

[0024] Since the lamp display part is composed of plural lamp groups and is larger than an attraction display device installed on a gaming apparatus, lighting /blinking control of each lamp carried out in accordance with an attraction mode determined by the link attraction mode determination means, is easily recognized distant from the gaming apparatus and a player can easily confirm at which gaming apparatus an attraction is being executed.

[0025] According to the present invention, a gaming system may comprise a plurality of gaming apparatuses, each of which has identification information. The gaming system comprises (a) first, second, and third gaming apparatuses, each of which executes a lottery of a prize pattern based on a predetermined input signal and pays what is earned to a player when a prize is generated, (b) a control and management device to store each gaming information sent from said each gaming apparatus, the each gaming information including identification information of the sending gaming apparatus, and (c) a display device provided to the each gaming apparatus to control an attraction display based on the stored gaming information; wherein said control and management device is provided with a link attraction determination device to determine an execution of a link attraction by referring to the stored gaming information.

[0026] The gaming system may be characterized in that said display means is provided with a lamp display part composed of a plurality of lamps such that the link

attraction is shown by blinking the lamps

[0027] In the gaming system, the first gaming apparatus may be closer to the second gaming apparatus than the third gaming apparatus. Therefore, the second gaming apparatus may have more probability to generate the prize than the third gaming apparatus when the prize is generated with the first gaming apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028]

Fig. 1 is a perspective view of a pachislot gaming machine of an embodiment

Fig. 2 is a block diagram showing a circuit for an operation of a pachislot gaming machine.

Fig. 3 is a block diagram showing a sub-control circuit.

Fig. 4 is an enlarged view of a display window.

Fig. 5 is a diagram showing a reel and back lamp.

Fig. 6 is a diagram showing series of symbols displayed along an outer peripheral surfaces of reels.

Fig. 7 is a diagram showing a symbol combination and a payout number of each prize pattern.

Fig. 8 is a diagram showing a stop table selected when an internal winning of bell prize pattern occurs.

Fig. 9 is a diagram showing a prize probability table.

Fig. 10 is a diagram showing commands sent from a main control circuit to a sub-control circuit.

Fig. 11 is a diagram showing a major memory area of a sub- RAM

Fig. 12 is a diagram showing a system configuration of a link attraction.

Fig. 13 is a diagram showing a positional relationship between a pachislot gaming machine and a gaming information display device

Fig. 14 is a front view of a gaming information display device

Fig. 15 shows an internal structure and patterns of a lamp display device in a lamp attraction mode ①.

Fig. 16 shows patterns of a lamp display device in a lamp attraction mode ②.

Fig. 17 shows patterns of a lamp display device in a lamp attraction mode ③.

Fig. 18 is a control block diagram of a gaming information display device.

Fig. 19 is a control block diagram of a management server.

Fig. 20 is a diagram showing data sent from a gaming information display device to a management server.

Fig. 21 is shows a BR generation and continuing number lottery table.

Fig. 22A shows a link attraction mode lottery table.

Fig. 22B shows a link attraction sending destination lottery table

Fig. 23 is a flow chart showing a process of a main

control circuit.

Fig. 24 is a flow chart showing a process of a main control circuit.

Fig. 25 is a flow chart showing a process of a main control circuit

Fig. 26 is a flow chart showing a lighting process of WIN lamp.

Fig. 27 is a flow chart showing an interrupt process 1.

Fig. 28 is a flow chart showing a sub-side main flow..

Fig. 29 is a flow chart showing an attraction control process at starting

Fig. 30 is a flow chart showing a BR generation lottery process

Fig. 31 is a flow chart showing a BR execution process.

Fig. 32 is a flow chart showing an attraction control process at stop

Fig. 33 is a flow chart showing a attraction control process when one gaming ends

Fig. 34 is a flow chart showing a BR parameter update process.

Fig. 35 is a flow chart showing an interrupt process 2.

Fig. 36 is a flow chart showing a button input process..

Fig. 37 is a flow chart showing a button input process

Fig. 38 is a flow chart showing a calling process

Fig. 39 is a flow chart showing a data receiving process on a gaming apparatus side.

Fig. 40 is a flow chart showing an attraction data sending and receiving process.

Fig. 41 is a flow chart showing a lamp attraction control process.

Fig. 42 is a flow chart showing an interrupt process 3.

Fig. 43 is a flow chart showing an attraction lottery process

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0029] Fig 1 is an external view of an embodiment of a gaming apparatus with stop buttons, a so-called pachislot gaming machine according to the present invention. A full door 3 is attached which is adapted to open and close to a plywood box-shaped cabinet 2 of a pachislot gaming apparatus 1. Above the full door 3, a gaming state display lamp 4 that lights up or flashes in different lighting manners corresponding to a bonus gaming, error and so on occurred, a speaker 5L and 5R generating effect sounds and error sounds during gaming, and a payout table 6 indicating payout numbers of each prize pattern and brief explanation of gaming are provided. A substantially vertical panel display part 7 is provided at the center of the full door 3, comprising three display

windows that have rectangular shape with vertical long (left display window 8L, middle display window 8C, right display window 8R) at the center, allowing reels (left reel 9L, middle reel 9C, right reel 9R) in the cabinet to be seen. These reels 9L, 9C and 9R have multiple symbols provided that can rotate freely on the outer peripheral surfaces, configuring a varying display means with display windows 8L, 8C and 8R.

[0030] On the left of the panel display part, a 1-BET lamp 10a to light up when one or more coins are bet, a 2-BET lamp 10b to light up when two or more coins are bet, and a 3-BET lamp 10c to light up when three or more coins are bet are provided. As the enlarged drawings of display windows 8L, 8C and 8R shown in Fig.4, when the 1-BET lamp 10a lights up, the center line L1 becomes an effective prize line (referred to as "enabled line" hereinafter), when the 2-BET lamp 10b lights up, the top line L2A and bottom line L2B are enabled as well as the center line L1 as an enabled line, when the 3-BET lamp 10c lights up, the cross down line L3A and cross up line L3B becomes enabled lines as well as the center line L1, top line L2A and the bottom line L2B

[0031] On the right of the panel display part 7, an in-bonus information display part 11, payout display part 13 are provided. The in-bonus information display part 11 is configured with 7 segment LEDs and informs proceeding status mostly of the bonus gaming. Under the display windows 8L, 8C and 8R, a liquid crystal display device 14 to display various gaming history and attractions

[0032] At the right side of the liquid crystal display device 14, a coin inlet 28 is provided. At the right side of the liquid crystal display device, a 1-BET switch 16, a 2-BET switch 17 and a MAXBET switch 18 are provided, beyond which a credit display part 25 is provided. If credited, one coin is bet in a game by depressing 1-BET switch 16 once. Two coins are bet in a game by depressing the 2-BET switch 17 once. Three coins that are the maximum number to be bet in a game are bet by depressing the MAXBET switch 18 once. As mentioned above, the predetermined prize line is enabled by operating these BET switches.

[0033] Among the 1-BET switch 16, the 2-BET switch 17 and the MAXBET switch 18, a cross button 19 to select and operate images such as gaming data displayed on the liquid crystal display device 14, a determination button 20 to confirm selected contents, and a cancel button 21 to cancel the selected contents and to return to a normal display from the selection screen or menu screen are provided.

[0034] Above the 1-BET switch 16 and the 2-BET switch 17, a credit display part 25 whose display part is configured with seven-segment LED is provided. Credit function is a function to reserve a range (for example, 50 coins) of coins in a gaming machine without paying out coins at prize. The credit display part 25 displays the number of currently reserved coins. Coins exceeding 50 are paid out to a coin tray 24.

[0035] A C/P (credit /payout) switch 22 for a player to switch receiving a payout or crediting the coins won in a game with an operation of a push button is provided at the left center of the full door 3. By the switching of the C/P switch 22, the coins paid out to the coin outlet 23 at the bottom of the full door, are reserved in the coin tray 24. A start lever 26 is provided so that it can be rotated freely within a predetermined angle at the right of C/P switch 22. When the start lever 26 is operated by a player, three reels 9L, 9C and 9R start rotating, and varying symbol display starts in the display window 8L, 8C and 8R.

[0036] At the center part of the full door 3, under the liquid crystal display device 14, a stop operation part 15 to stop the rotating three reels 9L, 9C and 9R one by one is provided constituting a stop means. The stop operation part 15 comprises a left stop button 27L, a middle stop button 27C and a right stop button 27R. A player can determine freely the order to depress these stop buttons 27L, 27C and 27R. In general, a stop operation carried out when all reels are rotating is called a "first stop operation", next stop operation is called a "second stop operation", and final stop operation is called a "third stop operation".

[0037] In this embodiment, depressing the left stop button 27L as the first stop operation is called a "normal depressing". Depressing the middle stop button 27C as the first stop operation is called a "middle depression". Depressing the right stop button 27R as a first stop operation is called a "reverse depression".

[0038] In the case of a gaming apparatus with three stop buttons, the total number of the stop operation order types is six. Operating the left stop button 27L as the first stop operation, the middle stop button 27C as the second stop operation and the right stop button 27R as the third stop operation is called "left middle right depression". Operating the middle stop button 27C as the first stop operation, the left stop button 27L as the second stop operation, right stop button 27R as the third stop operation is called "middle left right depression". Operating the middle stop button 27C as the first stop operation, the right stop button 27R as the second stop operation, the left stop button 27L as the third stop operation is called "middle right left depression". Operating the left stop button 27L as the first stop operation, right stop button 27R as the second stop operation and the middle stop button 27C as the third stop operation is called "left-right- middle depression". Operating the right stop button 27R as the first stop operation, the left stop button 27L as the second stop operation, the middle stop button 27C as third stop operation is called "right-left- middle depression". Operating the right stop button 27R as the first stop operation, the middle stop button 27C as the second stop operation and the left stop button 27L as the third stop operation is called "right-middle-left depression". A coin slot 28 is provided at the middle part of the full door 3 and right side of the liquid crystal display device 14.

[0039] Fig.2 is a block diagram of a circuit to realize the operation of the pachislot gaming machine 1 shown in Fig. 1 The gaming control means of this embodiment is configured of major two control circuits. A main control circuit 101 controls various types of peripheral devices connected electrically based on input signal from various detection means. A sub-control circuit 201 controls the gaming information sent from the main control circuit 101, attraction images displayed on the liquid crystal display device 14 based on the input signals from the cross button 19, determination button 20 and cancel button 21, and sound effects generated from the speaker 5L and 5R.

[0040] The main control circuit 101 is composed mainly of a microcomputer 102 setup on the circuit board with a circuit for random number sampling. The microcomputer 102 comprises the ROM104 in which gaming program and data are stored in advance, the CPU103 to carry out control operations according to the gaming program of the ROM104 and the RAM 105 to offer a working area required for the control process.

[0041] A clock pulse generating circuit 106 and a frequency divider 107 to generate standard clock pulse, a random number generator 108 to generate random numbers to be sampled, and a sampling circuit 109 to sample random numbers based on signals from a start lever 26 to be described below are connected to the CPU103. Random number sampling may be carried out in the microcomputer 102 by software processing. In that case, the random number generator 108 and the sampling circuit 109 may be omitted.

[0042] A control program to control various operations of a pachislot gaming machine, a prize probability table to be used for judging whether a random number obtained based on an operation of the start lever 26 is won or not, a stop table to determine the stopping position of reels 9L, 9C and 9R depending on the operations of stop button 27L, 27C and 27R, various gaming information commands to the sub-control circuit 201 in the probability lottery process described below are stored on ROM104 of the microcomputer 102. Various peripheral devices (actuator) are connected to the CPU103 via I/O port 110.

[0043] A motor driving circuit 111 controls stepping motors 112L, 112C and 112R to rotate reels 9L, 9C and 9R respectively depending on driving signals from the CPU103. Moreover, the motor driving circuit 111 controls to stop the stepping motors 112L, 112C and 112R according to the stop control signal from the CPU103.

[0044] The hopper driving circuit 113 controls drive of a hopper 114 as a coin payout device based on the payout command from the CPU103.

[0045] The seven-segment driving circuit 115 controls driving of various display part (payout display part 13, credit display part 25, in-bonus display part 11) configured with the seven-segment LED.

[0046] The lamp driving circuit 116 controls driving of various display parts (1-BET lamp 10a, 2-BET lamp 10b,

"MAXBET (3-BET) lamp 10c, WIN lamp 12) configured with lamps. Lighting of the WIN lamp 12 is configured in such a manner that it cannot be seen from the outside of the gaming apparatus.

[0047] There are other display devices such as liquid crystal display device 14 and reel backlight to be described below. The drive of them is controlled with the sub-control circuit 201.

[0048] Major input signal generation means of the microcomputer 102 to generate control signals required for input signals to each driving circuit includes a start lever 26, the 1-BET switch 16, the 2-BET switch 17, the MAX-BET switch 18, the C/P switch 22, an inlet coin sensor 117, a reel stop signals circuit 118, a reel index detection circuit 122, a payout detection circuit 119. They are also connected to the CPU103 via I/O port 110.

[0049] The start lever 26 detects a start operation by a player. The inlet coin sensor 117 detects coins that were inlet from the coin slot 28 and passed through a selector to screen irregular coins. The reel stop signals circuit 118 generates stop signals by detecting each stop button 9L, 9C and 9R are operated. The reel index detection circuit 122 supplies the CPU103 with symbol position reset signals by receiving signals from a rotation reference position detection switch in a stepping motor. The payout detection circuit 119 supplies the CPU103 with payout number signals by receiving signals from a coin detection part 120 in the hopper 114.

[0050] The method to control each driving circuit in the flow of a series of a game will be explained now. At first, the random number generator 108 generates random numbers in a certain numerical range since a power switch of the pachislot gaming machine 1 is turned on. If the inlet coin sensor 117 detects coin inlet by a player or coins are credited, the 1-BET lamp 10a, the 2-BET lamp 10b and the 3-BET lamp 10c are driven by the lamp driving circuit 116 to light up depending on the bet operations of the 1-BET switch 16, the 2-BET switch 17 and the MAXBET switch 18. When the start lever 26 detects a gaming start operation by a player, the sampling circuit 109 starts sampling of a random number value. The sampled random number value and the prize probability table stored on the ROM104 are cross-checked. If it is won, a winning flag for the related prize pattern becomes on. Such lottery process on the basis of software is called "probability lottery process". Details are to be described below.

[0051] Drive pulses are supplied to each stepping motor 112L, 112C and 112R via the motor driving circuit 111 and each reels of 9L, 9C and 9R starts rotating. The CPU103 monitors drive pulses supplied and updates a "pulse counter" secured in the RAM 105. The pulse counter value is monitored, and if it becomes a predetermined value, a symbol is considered to move by one symbol (also referred to as "one frame"), and the "symbol counter" secured in the RAM 105 is counted up by one count.

[0052] For example, if a stepping motor performs one

rotation at 1-2 phase excitation 400 pulse and 21 symbols are arranged on an outer peripheral surface of a reel, since a symbol moves by one frame by about 19 pulses, the CPU103 judges a symbol moved by one frame and counts up the "symbol counter" by one count.

[0053] On the other hand, in reels 9L, 9C and 9R, each time when the reference point of a symbol passes the center line L1 of the display window 8, an index detection signal is generated and a reset pulse is input to the CPU 103 through the reel index detection circuit 122. The CPU103 that detected the input of the reset pulse, clears the symbol counter that is counted up with the RAM 105. Consistency between a symbol position recognized on a software basis and the one actually displayed in the display window 8 is ensured.

[0054] When the reels 9L, 9C and 9R go into a constant speed rotation state after a given length of time has passed since they started rotating, the operation of the stop buttons 27L, 27C and 27R are enabled. When a player carries out a stop operation, a reel stop signal is inputted to the CPU103 via the reel stop signals circuit 118. After a processing on a software basis such as selection of a stop position, a stop pulse is supplied to the stepping motor 112L, 112C and 112R via the motor driving circuit 111 and reels 9L, 9C and 9R are controlled to stop.

[0055] In carrying out the stop control of the reels 9L, 9C and 9R, the CPU103 stores a code number of a symbol on the center line L1 as a stop operation position on a predetermined area of the RAM 105 when a stop signal from the reel stop signal circuit 118, refers to a stop table that associates the stop operation position with the center line L1. Then the CPU103 stores a symbol stop position corresponding to a stop operation position in a predetermined area of the RAM 105, calculates the number of pulses (frames) to be supplied to stop a intended symbol, and carries out a stop control after supplying pulses of a calculated number.

[0056] If the reels 9L, 9C and 9R are all stopped, a prize search is carried out. In a prize search, a symbol table stored on the ROM104 and a symbol stop position stored on the RAM 105 are cross-checked with each other, and a stop mode of a current game stopped in the display window 8L, 8C and 8R is provided. A symbol table is configured corresponding to a symbol column painted on a outer peripheral surface of the reels 9L, 9C and 9R to associate a code number indicating an order of a symbol from a reference position with a symbol code provided corresponding to the code number and play a role of a reel band on a software basis. Then, for each effective line L1, L2A, L2B, L3A and L3B, the stop mode and a prize symbol combination table stored on the ROM104 are cross-checked with each other to judge existence of a prize. A prize symbol combination table relates a prize symbol combination to the number of dividend coins in prize. The prize symbol is switched in order to change a prize symbol combination or dividend coin number depending on a gaming state.

[0057] The CPU103 pays out predetermined number of coins from the hopper 114 by supplying a payout signal to the hopper driving circuit 113 if "prize" is judged in a prize search. At that time, the coin detection part 123 calculates the number of coins that are paid out from the hopper 114 and stops the driving signal to the hopper driving circuit and a payout of coins if the calculated number reaches a predetermined number.

[0058] The block diagram in Fig.3 shows a configuration of a sub-control circuit 201. The sub-control circuit 201 controls peripheral devices for attraction such as the liquid crystal display device 14, speaker 5L and 5R based on gaming information from the main control circuit 101, and inputs from the cross button 19, determination button 20 and cancel button 21.

[0059] This sub-control circuit 201 is configured with a sub-microcomputer as a main component, image control circuit 250 to control the liquid crystal display device 14, sound source IC 230 to control sound from the speaker 5L and 5R, power amp 231 as an amplifier, and reel back lamp control circuit 240. These control circuits are configured with other circuit boards than the main control circuit.

[0060] The sub-microcomputer 202 comprises the sub-CPU203, the sub-ROM204 as a saving means and sub-RAM 205. The sub-control circuit 201 shown in Fig. 3 comprises a clock pulse generating circuit, frequency divider, random number generator, sampling circuit as the main control circuit though they are not shown. The sub-ROM204 stores a communication sequence program with the main control circuit 101, an attraction selection table to select various attractions based on received gaming information and sound sequence program. The sub-RAM 205 is used as a working area to carry out these control programs.

[0061] The sub-CPU203 determines an attraction to be carried out by various attraction control circuits based on a gaming information command sent from the main control circuit 101 and sends the determined contents to each attraction control circuit.

[0062] The image control circuit 250 is configured with an image control the CPU251, an image control ROM252, an image control RAM 253, an image ROM255, a video RAM 256 and an image control IC 254. The image control CPU251 receives a parameter determined by the sub-microcomputer 202 through the image control circuit IN port 257, and determines the display contents on the liquid crystal display device 14 in accordance with the image control sequence program stored on image control ROM252. The image control ROM252 stores a receipt sequence program of an image attraction command sent from the sub-microcomputer 202, image control sequence program to control the image control IC 254. The image control RAM 253 is used as a working area when carrying out an image control program.

[0063] The image control IC 254 forms images corresponding to display contents determined by the image

control CPU251 using graphic data stored on the image ROM255, stores them on the video RAM 256 temporarily, outputs them on the liquid crystal display device 14 in time via the image control circuit OUT port 258 to carry out display attractions.

[0064] The outer communication control circuit 259 outputs lighting information of the WIN lamp 12 controlled by the main control circuit 101 via lamp driving circuit 116 and gaming information sent from the sub-CPU through island LAN to be described below.

[0065] The reel back lamp control circuit 240 is used for attraction display control such as prize attraction and winning flag announcement. Fig.5 is an enlarged drawing of the reels 9L, 9C and 9R. The reel bands 29L, 29C and 29R of the reels 9L, 9C and 9R are configured with a semi-translucent film material, symbols such as "cherry", "7" are printed on the surface with light transmittance inks. Regions other than the symbols are masked with light shielding inks. At the back of the reel bands 29L, 29C and 29R, lamp housings 30L, 30C and 30R are provided so that lighting of each lamp may not interfere with other symbol regions. The reel back lamps 31 L, 31 C and 31 R are contained in each chamber of the lamp housings 30L, 30C and 30R. The reel back lamp control circuit 240 controls blinking of reel back lamps 31L, 31C and 31R based on a parameter determined by sub-microcomputer 202. It suggests a player of a prize symbol to be aimed, for example, by controlling blinking of reel back lamps 31L, 31C and 31R on the prize line when coins are paid out or preparing different blinking modes by internal prize pattern and executing an attraction display when a winning flag is established.

[0066] Fig.6 is a drawing in which the reel bands 29L, 29C and 29R are developed out on the flat. Each reel has 21 symbols. Each symbol has a symbol number from 1 to 21. They are stored on the ROM104 as a symbol table. The symbol columns 9L, 9C and 9R are variably displayed accompanying the rotation drive of the reels 9L, 9C and 9R. in the order of the symbol number (increasing order).

[0067] Fig.7 shows dividend coin numbers for prize symbol combinations (prize pattern) in each gaming state.

[0068] Internal winning, prize and gaming state will be explained now. Internal winning is a state wherein a winning is judged by cross-checking a sampled random number value and a prize probability table, and a winning flag of a related prize pattern is on in aforementioned probability lottery process. In general, a winning flag exists for all prize patterns. However, it is effective only established games. Winning flags are roughly categorized into a so-called small prize pattern with a comparatively smaller payout number wherein a winning flag is not carried over to the next game and a so-called bonus pattern wherein a winning flag is carried over until an prize is generated and internal lottery probability of prize patterns such as a big bonus (BB) or regular bonus (RB) is raised, and a large number of coin payout can

"be obtained.

[0069] Small prize patterns include, for example, "cherry" prize pattern that is won only by stopping on the effective line of the left reel, "bell" prize pattern or "watermelon" prize pattern that is on when three symbols stop on the effective line. Bonus prize patterns include a big bonus and regular bonus. The regular bonus (RB) is generated, for example, "BAR-BAR-BAR" is aligned on an effective winning line and pays out 15 coins in a prize.. It continues until a bonus game (of one coin bet called JAC game or pattern gaming) is played 12 times or prize is generated eight times. A big bonus (BB) is generated when, for example, "red 7-red 7-red 7" are aligned on the effective line.. It pays out 15 coins when prize. During a big bonus, small prize patterns such as so-called general gaming, and gaming with the prize probability of RB increased can be played up to 30 times.. During the game, RB can be played up to three times An RB prize from a general gaming is generated when, for example, "BAR-BAR-BAR" is aligned. A RB prize from a general gaming during BB is generated when "Replay-Replay-Replay" are aligned. When a replay prize pattern is won, the same number of coins as inlet coins is inserted automatically. Therefore, a player can play a game without inserting coins in the next game.. A single bonus (SB) is generated when, for example, "7 with sword-with sword-7 with sword" are aligned on the effective line. It pays out 15 coins when it is won. JAC game can be carried out once. Though the SB has a name of "bonus", a winning flag is not carried over The winning flag is effective only in the current game as a small prize pattern.

[0070] Gaming states will be explained now. The gaming states can be roughly categorized into three states depending on existence of a winning flag of bonus prize pattern, including the general gaming state wherein no bonus pattern has been won even in an internal lottery, the bonus internal winning state wherein, though there has been an internal winning in a probability lottery process, no prize has been generated with no bonus winning symbol aligned on the effective line (also referred to as "internally won bonus" or "internally hit bonus"), and bonus gaming state wherein prize symbols have been aligned on the effective line during bonus internal winning and a bonus gaming is played (also referred to as "enabled bonus")

[0071] Further, the internally won bonus is categorized into internally won BB and internally won RB depending on the bonus categories. Enabled bonus is categorized into enabled BB and enabled RB.

[0072] There are gaming states that are advantageous for a player to obtain a large number of coins other than bonus prize pattern.

[0073] For example, a specific state is known in which a high probability table (for example SB internal winning probability 1/2) and low probability table (for example SB internal winning probability 1/20) are prepared for an prize probability table of SB during the general gaming,

so-called "concentrated apparatus". Then a lottery to switch to a high probability table is carried out when using a low probability table (referred to as "plunge lottery"), on the contrary, a lottery to switch to a low probability table is carried out when a high probability table used (generally referred to as "puncture lottery"), and coins increase gradually

[0074] In addition, a specific state called "AT (assist time) function" is known. In the specific state, multiple prize patterns that can never be won at the same time are set (for example, prize patterns such as "bell-bell-red 7", "bell-bell-blue 7" and "bell-bell-white 7" are provided, with four frames or over interval of symbols such as "red 7", "blue 7" and "white 7" on the right reel). In a normal state, categories of internal prize pattern are not informed, so which "7" to be aimed is unknown, theoretically, prize 1/3 is only possible after the internal winning.. However, in the state to inform internal winning categories called "AT period", categories of "7" symbol to be aimed is known, theoretically, prize is possible at 100% after the internal winning only if aiming is correct, and the coins increase gradually

[0075] There is an "ST (super-time) function" in which a stop control is carried out with no prize pattern aligned unless predetermined stop order is carried out against the internal prize pattern of 1 even if a prize pattern is internally won and precise frame press is performed For example, as shown in Fig.8, 6 types of stop order table from "NO.1" to "NO.6" are prepared, when a bell is internally won in a probability lottery process, a stop table to be used is selected with a random number lottery and so on For example, in a current game, if a table stop table "NO.3" is selected, an winning is generated when middle stop button 27C, left stop button 27L and right reel stop button 27R are pressed in the first, second and third stop operation, respectively.. For other 5 types of stop order, a stop control wherein bell symbols are not aligned on the effective line even if a bell is internally won is carried out.

[0076] In a normal state, since this stop order is not informed, theoretically, prize is restricted to 1/6 after an internal winning. However, a state called ST period in which categories of a selected stop table is informed is known. In other words, when attaining the state in which an order to be stopped should be informed, theoretically, it is known that the 100 % winning is possible after internal winning and coins gradually increase.

[0077] As shown in Fig.7, the dividend coin number is different depending on gaming states even if a prize symbol is the same. For example, watermelon prize pattern has a payout of three coins during a general gaming and internally won bonus. However, it has a payout of 15 coins in general gaming during BB. "Replay-replay-replay" is a replay prize symbol during general gaming and internally won bonus.. However, it is RB prize symbol in a general gaming during BB. It is prize-pattern prize symbol of 15 payout in the JAC game.

[0078] Further, in this embodiment, aforementioned

"ST" is adopted as an advantageous status for a player other than bonus prize pattern. The ST gaming is configured in such a manner that it is activated if predetermined conditions are fulfilled during a general gaming. Specifically, when the SB prize pattern or the bell prize pattern is won internally, information about stop order required for aligning combination of symbols to be won in each prize pattern is announced to a player. Therefore, when the SB prize pattern or bell prize pattern is internally won during the period of this specific state, a player can surely generate winning without generating a failure by operation in accordance with the stop order announced

[0079] Fig. 9 is a diagram showing a prize probability table used in aforementioned probability lottery process. A random number value is extracted in the range of "0 to 16383". If it belongs to a winning range specified to each prize pattern, a related prize pattern wins an internal winning. For example, a random number value extracted in a current game is "10000", since it belongs to the winning range "2299" to "11024" of the bell prize pattern, the bell prize pattern is won internally. If a random number value extracted in a current game is "15000", since it belongs to the range of loss "13669 to 16383", no prize pattern is won internally resulting in loss..

[0080] Fig. 10 is a diagram showing a table of gaming information command from the main control circuit 101. In this embodiment, the main control circuit 101 to control prize judge and coin payout and the sub-control circuit 201 to control liquid crystal display device 14 and speaker 5L and 5R are configured with separate boards. Since gaming information about internal winning states of prize patterns and reel stop statuses processed in the main control circuit are required for an prize attraction processed by the sub-control circuit 201 and attraction control of a particular game, so-called battle rush (BR), both boards are connected to each other with a straight cable to sequentially send required information.. Sent commands include "start command" sent when a player operates the start lever 26, "reel stop command" sent when operating stop button 27L, 27C and 27R to stop rotating reels 9L, 9C and 9R, "1 gaming completion command" sent when one gaming is fully completed. Each command denotes a type of data in 2 bites. An anticipatory bite denotes the type and succeeding bite denotes the contents of the command. A start command is configured with six bites data. Data types include four types including "internal winning pattern", "gaming state", "selected stop table" and "inlet coin number". The reel stop command for one time stop operation is configured with four bite data. Data types include two types including "stop order" and "stop reel".. The one gaming completion command is configured with four bite data. Data types include two types including "prize categories" and "bonus gaming state".

[0081] Fig. 11 is a diagram showing major working area of the sub-RAM 205.. A reception flag is a storage region of the gaming information command sent from

the main control circuit 101. The BR continuance time number counter is a counter to show the number of the remaining games of BR, which is a particular game.. A BR flag is a flag to identify BR generated by a winning of BR generation lottery process and BR currently generated. BR evacuation flag is a flag to identify that a bonus is internally won during BR and BR is interrupted. The random number for the attraction lottery process is a storage region for random numbers used for various lottery processes.

[0082] Fig. 12 is a diagram showing a link attraction system. The pachislot gaming machine 1 installed in pachinko parlors or game parlors (hereinafter abbreviated to be "parlors") forms a gaming apparatus island 50 consisted of 5 to 20 units of gaming apparatuses. A system of supply and collection of gaming media for each gaming apparatus is configured with a unit of the island. Each pachislot gaming machine 1 is provided with an outer communication control circuit 259 as a means to connect to outer networks, which collect gaming information and WIN lamp operation information output from the main control circuit 101 and sub-control circuit 201 in the gaming apparatus island control means 52, which executes control and management of the communication sequence with a unit of the island, through island LAN (Local Area Network) 51 and sends them to the management server 54. The management server 54 is connected to Internet 55 and configured in such a manner that it can send and receive data from servers outside the parlor.

[0083] The management server 54 determines gaming apparatus unit (unit number) to send the current attraction mode and link attraction mode by a link attraction determination means to be described hereinafter configured with link attraction mode lottery table, and sends attraction information to gaming apparatus island control means as a sending destination. The gaming apparatus island 50 is configured with pachislot gaming machine 1 allotted with unit numbers from A to E and a gaming information display device to be hereinafter described. The gaming apparatus unit determined as the sending destination of the link attraction is identified by this unit number information. The gaming apparatus island control means 52 analyzes received data and send attraction data to each gaming information display device 80.

[0084] Fig. 13 is a diagram showing positional relationship between pachislot gaming machine 1 and, gaming information display device 80. In general pachinko parlors, a gaming information display device 80 is installed corresponding to each gaming apparatus as a standard for selection of a gaming apparatus, showing number of big prizes and carried out games. In general, a gaming information display device 80 is installed at the upper part of the pachislot gaming machine 1. The gaming information corresponding to a gaming apparatus is sequentially displayed and updated. The gaming information display device 80 is con-

connected to the management server 54 through the island LAN 51 to relay gaming information from the pachislot gaming machine 1.

[0085] Fig. 14 is an external view of the gaming information display device 80. The gaming information display device 80 is configured with a lamp display part 81L, 81 R including a lamp board with a lamp board covered with a transparent acrylic cover, and an information display part 82 constituted of a liquid crystal display device. At the lower part of the lamp display part 81 L and 81 R, there are provided a call button 83 to call shop assistants in case of requiring calling assistants such as coin clogging or hopper empty generating, to make lamp display part 81L, 81 R blink in the mode of calling, and a switching button 84 to switch gaming information displayed on the information display part 82 to the past records. Calling button 83 lights up in the calling blinking mode by pressing once. It stops blinking by pressing once again.

[0086] Under the information display part 82, a left scroll button 85 to left-scroll the display contents to change and right-scroll button 86 to right-scroll to change display contents are provided.

[0087] Fig. 15 is a diagram showing an inner structure of the lamp display part 81L and 81 R of the gaming information display device 80, and the lamp attraction mode (1) carried out by the lamp display part 81L and 81R. Nine lamps are provided in the lamp housing 89 sectioned by a light shield wall in the lamp display part 81L and 81R. Each lamp is installed on the lamp board 88L of the lamp display part 81L and lamp board 88R of the lamp display part 81 R.

[0088] Shaded areas of the diagram represent the state of lighted lamps. Other parts denote light-off lamps. The numbers on the lower right represent displayed time. In the attraction mode of lamp attraction mode (1), first, the lamp 1a lights up for 200ms in left upper row of the left side lamp display part 81L, then, lamp 2b lights up for 200ms in middle row of the left side lamp display part 81L, then, the lamp 3c lights up for 200ms in the right lower row of the left side lamp display part 81L, then the lamp 4c in left lower row of the right side lamp display part 81 R, then, the lamp 5b lights up for 200ms in the middle row of the right side lamp display part 81 R, finally, the lamp 6a lights up for 200ms in the upper right row of the right side lamp display part 81 R to complete one attraction.

[0089] Fig. 16 is a diagram showing the lamp attraction mode (2). First, lamps in the left upper row 1a, left middle row 1b, left lower row 1c of the left side lamp display part 81L light up for 200ms, then lamps light up for 200ms in the right upper row 6a, right middle row 6b and right lower row 6c of the right side lamp display part 81 Rs, then, lamps light up for 200ms in the middle upper row 2a, middle row 2b and middle lower row 2c of the left side lamp display part 81L, then, lamps light up for 200ms in the middle upper row 5a, middle row 5b, middle lower row 5c of the right side lamp display part 81

R, then, lamps light up for 200ms in the right upper row 3a, right middle row 3b and right lower row 3c of the left side lamp display part 81 L, finally, lamps lights up for 200ms in the left upper row 4a, left middle row 4b and left lower row 4c of the right side lamp display part 81 R to complete one attraction.

[0090] Fig 17 is a diagram showing lamp attraction mode (3). First, lamps in the left lower row 1 c, middle lower row 2c, right lower row 3c of the left side lamp display part 81 L and lamp in the left lower row 4c, middle lower row 5c, right lower row 6c of the right side lamp display part 81 R light up for 200ms, then, lamps in the left middle row 1b, middle row 2b, right middle row 3b of the left side lamp display part 81L, and lamps in the left middle row 4b, middle row 5b, right middle row 6b of the right side lamp display part 81R light up for 200ms, then, lamps in the left upper row 1a, middle upper row 2a, right upper row 3a of the left side lamp display part 81 L and lamps in the left upper row 4a, middle upper row 5a, right upper row 6a of the right side lamp display part 81 R light up for 200ms, then, lamps in the left upper row 1a, middle upper row 2a, right upper row 3a of the left side lamp display part 81 L and lamps in the left upper row 4a, middle upper row 5a, right upper row 6a of the right side lamp display part 81 R light up for 200ms, then, lamps in the left middle row 1 b, middle row 2b, right middle row 3b of the left side lamp display part 81 L and the lamps in the left middle row 4b, middle row 5b, right middle row 6b of the right side lamp display part 81R light up for 200ms, finally, lamps in the left lower row 1c, middle lower row 2c and right lower row 3c of the left side lamp display part 81L and Lamps in the left lower row 4c, middle lower row 5c, right lower row 6c of the right side lamp display part 81 R light up for 200ms to complete one attraction.

[0091] Fig. 18 is a block diagram of the gaming information display device 80. The gaming information display device is composed of a WIN lamp detection block to detect WIN lamp 12 to light up, an outer communication control block to control communication with the management server 54 via island LAN 51, an attraction control block to control attraction of lamp display part 81 and information display part 82 built in the main body of the gaming information display device 80, gaming apparatus communication block to control communication with pachislot gaming machine 1, operation detection block to detect inputs from various operation buttons, and gaming information display device main control block to totally control each block.

[0092] The WIN lamp detection block is composed of a photo acceptance part 140, installed near the WIN lamp, having a photo acceptance element to detect light generated by a lamp, and an optical communication control part 141 to send the detection signals from photo acceptance part 140 to the main control part via a filter circuit and an amplification circuit.

[0093] The outer communication control part 143 of the outer communication control part block is composed

of an Ethernet (registered trademark) control part, (not shown), an IP control part to control Internet protocol, a TCP control part to control the transmission control protocol, and a DHCP client part to carry out client processing of dynamic host configuration protocol (DHCP) in order to carry out address assignment to each gaming information display device (gaming apparatus) and communication control by Internet protocol (TCP/IP) in the gaming apparatus island control means 52 described hereinafter.

[0094] The attraction control part 144 is provided with a function to control the lamp display part in a predetermined attraction mode when carrying out shop clerk calling operation or the link attraction mode is determined in the management server 54 and the like, a link attraction mode is determined and attraction data is sent via gaming apparatus island control means 52, and a function to display gaming information such as numbers of games and big prizes on the information display part 82.

[0095] The gaming apparatus side input part 145 processes gaming information received from an outer communication control circuit 259 of the pachislot gaming machine 1. Specific examples of gaming information include gaming history such as numbers of game and big prizes.

[0096] The operation input part 146 receives the input signals sent and relays the data to the gaming information display device main control part 147 when various input devices, calling button 83, display switching button 84, left scroll button 85, right scroll button 86 provided in the gaming information display device 80 are operated.

[0097] The gaming information display device main control part 147 comprises a gaming information display device microcomputer 151 composed of a gaming information display device CPU 148 (referred to as "gaming history CPU" hereinafter), gaming information display device ROM 149 (referred to as lower "gaming history CPU" hereinafter) and gaming information display device the RAM 150 (referred to as lower "gaming history CPU" hereinafter) and totally controls function blocks such as send and receive of the gaming information and attraction data, acceptance of operation of calling button 83 and scroll buttons 85 and 86.

[0098] Fig. 19 shows a control block diagram of the management server 54. The management server 54 receives data sent from the LAN 53 in the parlor via input/output part 160 at the management server communication control part 161. Each one of the received transmission data is analyzed at the management server main control part 162. If it is a general gaming information, a link attraction mode is determined by referring to update of the gaming information database 163 used as business data and link attraction mode lottery table stored on a storing means 164 for the link attraction. If it is a WIN lamp lighting information, link attraction transmission destination (unit number) is determined and transmission processing of the attraction data is carried out

referring to link attraction transmission destination lottery table stored on link attraction data stored on storing means 164. If it is a calling information or error information, a transmission processing of messages to prompt confirmation of related gaming unit to the portable communication terminal carried by parlor staffs is executed.

[0099] The display control part 165 displays various information on the monitor 166 in such a manner that manager can monitor the situation.

[0100] The management server main control part 162 is composed of a management microcomputer 167 composed of a management server CPU 168 (referred to as "management the CPU" hereinafter), management server ROM 169 (referred to as "management ROM") and management server the RAM 170 (referred to as "management RAM") and transmits or receives data and determines a lamp attraction mode based on a predetermined sequence program.

[0101] Fig. 20 is a diagram showing detailed data sent from the gaming information display device 80 to the management server based on the gaming information generated from the pachislot gaming machine 1. Transmitted data in common has information of an unit number of a sender gaming apparatus (unit). The transmitted data contains the game start information, coin inlet information, coin payout information, bonus prize generation information, bonus gaming completion information, bonus internal winning information, WIN lamp lighting information to identify WIN lamp lighting status, calling information generated by the operation of gaming information display device 80, error information generated when a misconduct is detected depending on gaming status.

[0102] Fig. 21 is a diagram showing a BR generation and BR continuance number lottery table. In this embodiment, whether a specific game BR is generated or not and the number of BR continuance are determined by lottery at a constant probability when a predetermined prize pattern is internally won.

[0103] In the table, BR is generated at the probability of 16/128 when a watermelon is internally won, 11/128 when two cherries internally won and 25/128 at loss.

[0104] Fig. 22 is a diagram showing a link attraction mode lottery table and link attraction transmission destination lottery table. In this embodiment, a link attraction determination process carried out in the management server 54 refers to it when the gaming information sent from each gaming apparatus includes bonus internal winning information, or WIN lamp lighting information.

[0105] Attraction transmission destinations are identified by unit number information A to E allotted to a pachislot gaming machine 1 and a gaming information display device accompanying to it.

[0106] The link lottery mode lottery table in Fig. 22 (a) determines a attraction mode to be carried out from the three types of link attraction modes shown in Figs. 15 to 17 depending on an established bonus prize pattern category and extracted random number if data sent

from a gaming information display device is a bonus internal winning information and internal winning flag is on. The table is configured in such a manner that, if an internal prize pattern is BB, the probability that the attraction mode ③ is selected is high, and if an internal prize pattern is RB, if the probability that attraction mode (1) is selected is high.

[0107] The link attraction transmission destination lottery table shown in Fig. 21 (b) determines a gaming apparatus (unit) to transmit the link attraction carrying out data depending on transmitting gaming machine types and extracted random number if the data sent from gaming information display device is WIN lamp lighting information and WIN lamp lighting flag is on. It is highly probable that a gaming apparatus selected as a transmission destination is near an original gaming apparatus. For example if WIN lamp lighting up is generated in the gaming apparatus "C", the probability of being a transmission destination gaming apparatus decreases in the order of the gaming apparatus same as the source "C" (random number range 64), the gaming apparatus "D" on the right of the transmission source gaming apparatus "C" (random number range 28), and the gaming unit "B" on the left of the transmission source gaming apparatus "C" (random number range 20) from highest to lowest.

[0108] In this configuration, it is possible to produce a sense of expectancy for bonus prize pattern also for players in the vicinity of the gaming apparatus executing the link attraction.

[0109] Then, control operation of the main control circuit 101 and the CPU103 will be explained referring to the main flow chart from Figs. 23 to 26.

[0110] At first, the CPU 103 carries out initialization before starting a game (step 301, referred to as ST hereinafter). Specifically, it carries out clearance of previous game status and communication data stored on the RAM 105, writing of gaming parameter required for a game, setting of a start address of a sequence program.

[0111] Then, the CPU 103 judges whether there is an automatic coin inlet request, in other words, judges whether there was a replay prize in the previous game (ST 302). If judged as "YES", coins requested are automatically inlet and goes to the process of ST 305. If ST 302 judges "NO", whether new coins were inserted or not, in other words, whether there is an input from the inlet coin sensor 117 due to coins inlet by a player into the coin slot 28, whether there is an input by the operation of various BET switches 16, 17 and 18 are judged (ST 304).

[0112] If this is judged "YES", goes to ST 305. If "NO", the input signal is monitored until BET operation is executed.

[0113] Then, the CPU 103 judges whether there is an input by the operation of the start lever 26 (ST 305). If judged as "YES", goes to ST 306, and if "NO", input signals are monitored until the start lever is operated.

[0114] Then, probability lottery process is carried out

(ST 306). In the probability lottery process, at first, random number values for a lottery is extracted in the range of "0 to 16383" using random number generator 108 and sampling circuit 109. A prize range to which an extracted random number belongs is judged by using an prize probability table (Fig. 9) that sets a random number value range (prize range) depending on the gaming state and inlet medal number and related internal prize pattern (winning flag) is determined. Then, if a determined winning flag is the SB prize pattern or bell prize pattern, a stop table to be used is determined.

[0115] A stop table is carried out by a random number lottery process using a probability table that has even random number range for six types of stop tables as shown in Fig.8.

[0116] Then, WIN lamp lighting process is carried out (ST 307). WIN lamp lighting process lights up WIN lamp 12 at a certain probability when a bonus prize patterns such as BB and RB are won internally. In this embodiment, a player cannot recognize lighting up of the WIN lamp. It plays a role as a starting trigger of a link attraction.

[0117] Then, gaming information of the main control circuit 101 is sent to the sub-control circuit when starting a gaming start (ST 308). Transmitted commands include, as shown in the "start command" the gaming information command table of the Fig. 26, a winning flag determined by the above-mentioned probability lottery process, current gaming state, stop table number determined depending on an winning flag and number of inlet coins.

[0118] Then, whether a predetermined time, for example 4.1 sec, has passed with the one game monitoring timer set in the previous game is judged (ST 309). If judged as "YES", one game monitoring timer for the following game is set (ST 311). If judged as "NO", one game monitoring timer is set for the following game (ST 311) after the remaining predetermined time is expired (ST 310).

[0119] Then, the CPU103 controls the motor driving circuit 111 and, carries out a rotation process of reels 9L, 9C and 9R (reel rotation process) (ST 312). Reel rotation process carries out an acceleration process starting from the state where the reels 9L, 9C and 9R stop, and constant-speed process after a predetermined speed is reached. The stop buttons 27L, 27C and 27R, and stop operation of the reels 9L, 9C and 9R are enabled on the condition of this constant-speed state.

[0120] Then, the CPU103 judges whether any one of stop buttons 27L, 27C and 27R was operated (is the stop button on?), in other words, whether there is any stop signals sent from the reel stop signals circuit 118 when a player operates the stop buttons 27L, 27C and 27R. If judged as "YES", goes to ST 315. If judged as "NO", goes to the process ST 314. The process ST 314 judges whether the value of the automatic stop timer is "0" or not. The automatic stop is a process to stop automatically the reels 9L, 9C and 9R after a predeter-

mined period of time (for example 40 seconds) has passed since the reels started rotating even if they are rotating because stop buttons 27L, 27C and 27R are not pressed. If judged as "YES", in other words, the automatic stop timer was "0", goes to ST 315 in order to automatically stop the reels. If judged as "NO", goes to process ST 313 in order to keep on monitoring reception of stop operations.

[0121] In the process ST 315, the CPU 103 carries out "slip frame number determination process". The "slip frame number determination process" determines the slip frame number of a reel corresponding to a stop button that received a stop operation, "slip frame number" used herein means the number of symbols (frame number) to be slipped before stopping the reel (actual stopped position is called "stop position") from the symbol position (referred to as "stop operation position") displayed in the display window 8L, 8C and 8 R when the stop buttons 27L, 27C and 27R were pressed.

[0122] Then, the CPU103 controls the motor driving circuit 111 so that a reel corresponding to a stop button that received a stop operation is stopped after rotating by determined number of slip frames (ST 316).

[0123] Then, the CPU103 transmits "reel stop command" indicating a reel has been stopped to the sub-control circuit 201 (ST 317).

[0124] The reel stop command, as shown in Fig.28 gaming information command "reel stop command", transmits the stop order status (What number of the current stop operation?) and, stop reel status (Which reel has received a stop operation?) to the sub-control circuit 201.

[0125] Then, the CPU103 judges whether all reels stopped or not. If judged as "YES", goes to ST 319. If judged as "NO", there remain some rotating reels and goes to ST 313.

[0126] Then, the CPU103 carries out a winning search process (ST 319). This winning search process judges whether a stop mode of a symbol

[0127] Displayed in the display windows 8L, 8C and 8 R denotes an established winning.. If it is a stop mode to denote an established winning, a winning flag of a related winning pattern is stored on the RAM 105. Specifically, a judgment is carried out by cross-checking a code number of a symbol on the center line L1 with the winning symbol combination table stored on the ROM104.

[0128] Then, a judgment is carried out by cross-checking an winning flag and won flag for matching to confirm the current winning is normal (ST 320) If this judged "NO", an "illegal error" is displayed. Execution of gaming program is interrupted. If ST 320 judged "YES", coins are paid out corresponding to the established winning pattern type and gaming status (ST 322).

[0129] Then, if a gaming state is changed by completing the current gaming, the migration process is carried out (ST 323). ST 323 includes the final winning of a bonus gaming, a bonus internally won by the current gam-

ing, start of bonus gaming by "7-7-7" and symbols stopped on the effective line.

[0130] Then, types of established winning pattern and gaming state, etc are sent to the sub-control circuit as "1 game completion command" as shown in the gaming command table of the Fig. 10 (ST 324).

[0131] Fig. 26 is a flow chart showing WIN lamp lighting process. First, the CPU 103 judges whether WIN lamp has already lighted up (ST 325). If judged as "YES", passes the process and returns to the main flow. If judged as "NO", then, whether a bonus is internally won is judged (ST 326). If judged as "NO", returns to the main flow because it is not required to turn on the WIN lamp. If judged as "YES", then, a lottery process to decide WIN lamp shall be turned on or not is carried out. The lottery is carried out by using WIN lamp lighting lottery table (winning probability 1/6) and lottery random number value stored on the ROM 104 (ST 327). Then, whether it is won in the lottery process is judged (ST 328). If the result of the judgment is "YES", WIN lamp 329 is turned on (ST 329) and returns to main flow. If judged as "NO", returns to the main flow without doing anything.

[0132] Then, control operation of the sub-CPU 203 of the sub-control circuit 201 will now be explained.

[0133] Fig. 27 is a flow chart showing the interrupt process 1. The interrupt process 1 is executed in the interrupt process per 3ms The interrupt process 1 carries out processes to store gaming information commands sent from the main control circuit 101 and input signals from the cross button 19, determination button 20, and cancel button 21 on the sub-RAM 205.

[0134] First, the sub-CPU 203 checks the input buffer (ST 400) and judges whether there is an input signal in the input buffer (ST 401). If judged as "YES", receiving flag is turned on (ST 402), contents of the received command are set to the sub-RAM 205 (ST 403), and the process is completed. If judged as "NO", the process is completed as it is.

[0135] Fig.28 is a diagram showing the main flow chart of the sub-control circuit side. First, the sub-CPU 203 checks the receiving flag of the sub-RAM 205.. As shown above, gaming information on the main control circuit 101 stored on the receiving flag include a start command generated when a player operates the start lever 26, a reel stop command generated when operating stop buttons 27L, 27C and 27R to stop rotating reels 9L, 9C and 9R, and a 1 gaming completion command generated after carrying out payment of coins in case of a prize to stop all reels. Various attraction processes are carried out by each command.

[0136] First, the sub-CPU 203 checks the receiving flag area in the sub-RAM 205, and judges whether there are input operations about the gaming support menu including the cross button 19, determination button 20, cancel button 21 and so on (ST 404). If judged as "NO", skips ST 405 and goes to ST 406.. If judged as "YES", it carries out processes corresponding to inputs includ-

ing display and edit of the support menu (ST 405).

[0137] Then, it judges whether a start command has been received (ST 406). If judged as "NO", it skips ST 407 and goes to ST 408. If judged as "YES", it executes an attraction control process at start (ST 407). This process carries out control process of BR if during BR. Details will be hereinafter described.

[0138] Then, it judges whether reel stop command is received or not. (ST 408). If judged as "NO", skips ST 409 and moves to ST 410, and if judged as "YES", it executes an attraction control process when stopping a reel (ST 409). This process carries out announcement of stopping order during BR generation lottery process and BR, and attraction corresponding to conformity between announcement contents and reel stop operation. Details will be hereinafter described.

[0139] Then, it judges whether 1 game completion command has been received or not (ST 410). If judged as "NO", it skips ST 411 and returns to process ST 404, repeats the same process. If judged as "YES", then, it executes attraction control process after 1 gaming completion (ST 411). This process updates BR continuance number, and outputs gaming information to the gaming state display device if during BR. Details are to be hereinafter described.

[0140] After the process ST 411 is completed, it returns to ST 404, and repeats the same process. Thus, the main flow chart of the sub-control circuit 201, based on the gaming information command sent from main control circuit 101, repeats a process to branch to related attraction processes.

[0141] Fig. 29 is a flow chart to show an attraction control process at start. The sub-CPU 203 carries out BR generation lottery process (ST 500). BR generation lottery process is a process to determine whether to generate battle rush as a specific game or not. Details are to be hereinafter described. Then, it carries out BR process (ST 530). BR execution process is to carry out stop order announcement during BR. Details are to be hereinafter described.

[0142] Fig. 30 is a flow chart showing the BR generation lottery process. First, the sub-CPU 203 checks BR flag stored on the sub-RAM 205 and judges whether it is during BR gaming or not (ST 501). If judged as "YES", it returns to the attraction control process at starting without doing anything. If judged as "NO", it judges whether any BR continuance number is won referring to BR generation lottery table shown in Fig. 21 (ST 502, 503). If judged as "NO" (loss), returns to the attraction control process at starting. If judged as "YES", it turns on the BR flag of the sub-RAM 205, sets a continuance number won in the BR continuance number (ST 504), carries out BR generation attraction (ST 505) and returns to attraction control process at starting.

[0143] Fig. 31 is a flow chart showing BR execution process. First, the sub-CPU 203 checks BR flag and BR evacuation flag of the sub-RAM 205 and judges whether it is during BR or bonus generated during BR and BR is

interrupted (ST 531). If judged as "NO", since it is not during BR, returns to the attraction control process at start without doing anything. If judged as "YES", it checks a receiving flag of the sub-RAM 205, and judges whether bonus prize pattern is internally won (ST 532). If judged as "YES", it interrupts BR, turns off BR flag and turns on BR evacuation flag of the sub-RAM 205 in order to digest bonus gaming (ST 533) and returns to attraction control process at start.

[0144] If ST 532 judges as "NO", then, in the case during BR evacuation, in order to restart BR, it turns off BR evacuation and turns on BR flag of the sub-RAM 205 (ST 534). Then, it checks BR continuance number of the sub-RAM 205 in order to judge whether BR continuance number has been all digested (ST 535). If judged as "YES", it means BR has been completed. It turns off BR flag (ST 536) returns to attraction control process at start.

[0145] If judged as "NO", a predetermined game number of BR has not been completed, then, it checks receiving flag of the sub-RAM 205 and judges whether bell or SB is won internally in the current game (ST 537). If judged as "YES", it announces an appropriate stop order referring to a selection stop table stored in the receiving flag of the sub-RAM 205 (ST 538) and returns to the attraction control process at start. If judged as "NO", it returns to the attraction control process at start without announcing anything.

[0146] Then, the attraction control process when stop buttons 27L, 27C and 27R are operated during BR will now be explained. Fig. 32 is a flow chart showing an attraction control process when a reel is stopped. First, the sub-CPU 203 checks BR flag of the sub-RAM 205 and judges whether it is during BR or not (ST 650). If judged as "NO", it returns to the sub-side main flow without doing anything. If judged as "YES", then, it checks the stop command of the receiving flag of the sub-RAM 205, cross-checks stop order data and stop reel data with used table No data, and judges whether the current stop operation corresponds to the correct press order (ST 651). If judged as "YES", it displays the stop operation was performed with a correct depression order (ST 652). If judged as "NO", it displays the stop operation was performed with an wrong depression order (ST 653), and returns to the sub-side main flow.

[0147] Then, attraction control process carried out after all reels have stopped will now be explained. Fig. 33 is a flow chart showing an attraction control process when one gaming has been finished. First, the sub-CPU 203 carries out BR parameter update process to update gaming parameter about BR (ST 700), then it sends the gaming information of the current game, specifically, inlet coin number, payout coin number, bonus internal winning information to the outer communication control circuit (ST 720), returns to sub-side main flow. The outer communication control circuit 259 subsequently sends the gaming information to the gaming information display device 80.

[0148] Fig. 34 is a flow chart showing BR parameter update process. First, the sub-CPU 203 checks 1 gaming completion command of receiving flag stored on the sub-RAM 205 and judges whether the current gaming state is during bonus or not (ST 701). If judged as "YES", it cannot be during BR and it returns to attraction control process of 1 gaming completion without doing anything. If judged as "NO", then, it checks BR flag stored on the sub-RAM 205 and judges whether it is during BR (ST 702). If judged as "NO", it returns to attraction control process of 1 gaming completion without doing anything. If judged as "YES", it reduces BR continuance number counter of the sub-RAM 205 (ST 703), and returns to attraction control process of 1 gaming completion.

[0149] Then, a control operation of the gaming information display device 80 will now be explained. Fig. 35 is a flow chart showing an interrupt process 2 carried out in the main control part 147 of the gaming information display device. The interrupt process 2 is executed by 3ms. First, gaming history CPU 148 carries out processes such as switching of display contents and data transmission to management server 54 based on the input signal from various input parts provided in such a manner that players can operate, for example, calling button 83 (ST 750). Then, it carries out a reception process of gaming information sent from outer communication control circuit 259 of the pachislot gaming machine 1 (ST 751). Then, it carries out the WIN lamp lighting signals input process to check whether WIN lamp lighting signal has been input (ST 752). Then, it carries out management server side data receipt and transmission process to carry out the receipt and transmission process, if there is attraction control data sent from the management server 54 via island LAN 51 or gaming information to send the management server 54 (ST 753). Then, it completes one interrupt process by executing liquid crystal screen display process (ST 754) and lamp attraction control process (ST 755) in accordance with various attraction data set in the steps shown above.

[0150] Fig. 36 is a flow chart showing a button input process. First, the gaming history CPU 147 checks the input port of the operation input part to which operation signals are input from operation input part 146 (ST 770) and judges whether there is operation input (ST 771). If judged as "NO", it returns to the interrupt process 2 without doing anything. If judged as "YES", it executes a process to judge the types of operations. First, it judges whether the operation type is calling button 83 (ST 772). If judged as "YES", it executes a calling process (ST 773) and returns to the interrupt process 2. If judged as "NO", then, it judges whether the operation type is the switching button 84 (ST 774). If judged as "YES", it executes a display content change process to change the contents of the information display part 82 into the past history of gaming (ST 775) and returns to interrupt process 2.

[0151] Then, it judges whether the operation type is the left scroll button 85 (ST 776). If judged as "YES", it

switches the display data type into left scroll (ST 777) and returns to the interrupt process 2. If judged as "NO", since remaining operation types are only right scroll button operation, it switches display data types to the left scroll (ST 778) and returns to the interrupt process 2.

[0152] Fig. 38 is a flow chart showing a calling process. First, the gaming history CPU 148 checks the calling flag stored on the gaming history RAM 150 and judges whether the calling button has been operated and being called (ST 780). If judged as "NO", it moves to ST 783 and executes lamp lighting process with the lamp lighting mode in the calling state (all lamps remain lighted) (ST 783), sets the calling information data with the calling button flag on to the island side output port of the management server (ST 784) and returns to the button input process. If judged as "YES", it means the current switching operation is a cancel operation, and it turns off the lights under lighting control (ST 781) and sets calling information set to island side output port in order to notify the management server of the cancelled calling (ST 784) and returns to button input process.

[0153] Fig. 39 is a flow chart showing gaming apparatus side data receipt process. First, the gaming history CPU 147 checks gaming apparatus side input port (ST 800) and judges whether there are gaming data sent from the outer communication control circuit 259 of the pachislot gaming machine 1 (ST 801). If judged as "YES", it stores the gaming data in a predetermined region of the gaming history the RAM 150 (ST 802) and sets gaming information data (Fig. 20) corresponding to gaming data to the island side output port in order to send it to the management server 54 (ST 803). If judged as "NO", it returns to interrupt process 2 without doing anything.

[0154] Fig. 40 is a flow chart showing attraction data receipt and transmission process. First, the gaming history CPU 147 checks the island side input port and judges whether there are attraction data sent from management server 54 (ST 821). If judged as "NO", it skips ST 822 and moves to ST 823. If judged as "YES", it stores the attraction data in a predetermined region of the gaming history RAM 150 and moves to ST 823.

[0155] Then, it checks the island side output port (ST 823) and judges whether there are gaming information data from the gaming information display device 80 to the management server 54 (ST 824). If judged as "NO", it skips ST 825 and returns to the interrupt process 2. If judged as "YES", it outputs the set gaming information data and returns to the interrupt process 2.

[0156] Fig. 41 is a flow chart showing the lamp attraction control process. First, the gaming history CPU 148 checks the lamp attraction flag stored in a predetermined region of the gaming history the RAM 150 (ST 840) and judges whether the attraction flag is on (ST 841). If judged as "NO", it returns to the interrupt process 2 without doing anything. If judged as "YES", it carries out an attraction in a related attraction mode among 3 types of attraction mode (ST 842) and returns to the in-

interrupt process 2.

[0157] Fig. 42 is a flow chart showing the interrupt process 3 executed in the management server 54. The interrupt process 3 is carried out every 3ms. First, the management CPU 168 checks the input port (ST 860) and judges whether transmission data from each gaming information display device have been received (ST 861) If judged as "NO", it terminates the process without doing anything. If judged as "YES", then, it stores and updates the received data in the gaming information database 163 (ST 862) and carries out an attraction lottery process (ST 863). Then, it judges whether the transmission flag stored in the predetermined region of the management the RAM 160 is on, in other words, it is the transmission timing of the determined attraction data (ST 864). If judged as "NO", it terminates the process without doing anything. If judged as "YES", it send data to the gaming information display device with a related unit number (ST 865) and terminates one time process.

[0158] Fig. 43 is a flow chart showing an attraction lottery process. First, the management CPU 168 judges whether the currently sent data is an internally won data (ST 865). If judged as "YES", then, it judges whether an attraction of a related gaming apparatus has been already determined, in other words, internal winning information of the related gaming unit has been received before receiving current data (ST 866). If judged as "YES", it returns to the interrupt process 3 without doing anything. If judged as "NO", it is the first reception after the internally won bonus. It determines a link attraction based on the link attraction mode lottery table stored in the link attraction data stored on means 164, and a unit number to send the link attraction determined in accordance with the link attraction sent unit lottery table and returns to the interrupt process 3.

[0159] If judged as "NO" in the judgment of ST 865, then, it judges whether the received data is WIN lamp lighting information (ST 868). If judged as "NO", it returns to the interrupt process 3 without doing anything. If judged as "YES", it is the transmission timing of the link attraction data, it turns on the transmission flag of the management the RAM 160 (ST 869) and returns to the interrupt process 3.

[0160] In this embodiment, as an example of specific games, advantageous status generated for players by resolving the problems was explained using ST period. In addition to the aforementioned AT and advantageous status for players, a won flag of specific prize pattern may be established or internal winning probability of a prize pattern may be increased.

[0161] According to the present invention, an internal winning attraction of a prize pattern is determined by referring to internal winning information sent from multiple gaming apparatuses. Since gaming results of other player instead of a player's own gaming results are referred to, a player finds difficulty in understanding a determination process of internal winging attraction, offering the element of surprise in the attraction timing and

enhancing the excitement of a game.

[0162] A player concentrates on internal winning attraction carried out in the other player's gaming apparatus next to him as well as his own gaming apparatus when considering whether his own gaming apparatus has internally won. For example, a player can have expectation that the internal prize pattern carried out in the gaming apparatus next to him has been in fact caused by the bonus internal winning information of his own gaming machine, offering enhanced excitement of the gaming.

Claims

1. A gaming system comprising:

- (a) a plurality of gaming apparatuses, each of which executes a lottery of a prize pattern based on a predetermined input signal and pays what is earned to a player when a prize is generated,
- (b) a control and management means for storing gaming information sent from said each gaming apparatus, and
- (c) a display means for controlling an attraction display based on the gaming information;

wherein said control and management means is provided with a link attraction determination means for determining an execution of a link attraction by referring to the gaming information.

2. The gaming system according to claim 1, wherein said display means is provided with a lamp display part composed of a plurality of lamps, and wherein the link attraction is shown by blinking the lamps.

3. A gaming system comprising:

- (a) a plurality of gaming apparatuses, each of which executes a lottery of a prize pattern based on a predetermined input signal and pays what is earned to a player when a prize is generated,
- (b) a gaming information display means for receiving and displaying gaming information sent from said each gaming apparatus, and
- (c) a control and management means for storing gaming information sent from said each gaming apparatus;

wherein said control and management means comprises

a link attraction determination means for deter-

mining an execution of a link attraction by referring to the gaming information and a link attraction transmission means for sending the link attraction determined by the link attraction determination means to said gaming information display means 5

4. The gaming system according to claim 3, wherein said gaming information display means is provided with a lamp display part composed of a plurality of lamps, and wherein the link attraction is displayed by blinking the lamps. 10
5. A gaming system comprising: 15
 - (a) first, second, and third gaming apparatuses, each of which executes a lottery of a prize pattern based on a predetermined input signal and pays what is earned to a player when a prize is generated, 20
 - (b) a control and management device to store each gaming information sent from said each gaming apparatus, the each gaming information including identification information of the sending gaming apparatus, and 25
 - (c) a display device provided to the each gaming apparatus to control an attraction display based on the stored gaming information; 30

wherein said control and management device is provided with a link attraction determination device to determine an execution of a link attraction by referring to the stored gaming information. 35
6. The gaming system according to claim 5, wherein said display means is provided with a lamp display part composed of a plurality of lamps, and wherein the link attraction is shown by blinking the lamps. 40
7. The gaming system according to claim 5, wherein the first gaming apparatus is closer to the second gaming apparatus than the third gaming apparatus, and 45

wherein the second gaming apparatus has more probability to generate the prize than the third gaming apparatus when the prize is generated with the first gaming apparatus.. 50

55

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

Left reel		Middle reel		Right reel	
21	Red 7	21	Red 7	21	Red 7
20	Cherry	20	Replay	20	Bell
19	Bell	19	Watermelon	19	Replay
18	Replay	18	7 with sword	18	7 with sword
17	7 with sword	17	Bell	17	Watermelon
16	Red 7	16	7 with sword	16	Bell
15	Bell	15	Replay	15	Replay
14	Replay	14	BAR	14	7 with sword
13	7 with sword	13	Bell	13	BAR
12	Cherry	12	7 with sword	12	Bell
11	Bell	11	Replay	11	Replay
10	Replay	10	Watermelon	10	7 with sword
9	BAR	9	BAR	9	Watermelon
8	7 with sword	8	Bell	8	Red 7
7	Bell	7	7 with sword	7	Bell
6	Replay	6	Replay	6	Replay
5	7 with sword	5	Cherry	5	7 with sword
4	Watermelon	4	Replay	4	Cherry
3	Bell	3	Bell	3	Bell
2	Replay	2	7 with sword	2	Replay
1	7 with sword	1	Bell	1	7 with sword
9L'		9C'		9R'	

Fig. 7

Symbol combination	In Common gaming (In bonus internal winning)	Common gaming in BB	JAC (pattern) gaming
Red 7—Red 7 —Red 7	15+BB		
BAR—BAR—BAR	15+RB		
7 with sword —7 with sword —7 with sword	15+SB		
Watermelon —Watermelon —Watermelon	3	15	
Bell—Bell—Bell	6	7	
Cherry —ANY—ANY	1	1	
Replay—Replay —Replay	Replay	1+RB	15

Fig. 8

Table No.	left middle right	left right middle	middle left right	middle right left	right left middle	right middle left
1	O	x	x	x	x	x
2	x	O	x	x	x	x
3	x	x	O	x	x	x
4	x	x	x	O	x	x
5	x	x	x	x	O	x
6	x	x	x	x	x	O

O... prize

x... not prize

* ... The timing of frame press is free.

Fig. 9

Winning pattern	Random number range	confirmation
SB	0~2298	2299/16384
Bell	2299~11024	8726/16384
Watermelon	11025~11165	141/16384
Cherry	11166~11385	220/16384
Replay	11386~13630	2245/16384
BB	13631~13668	38/16384
RB	13669~13696	27/16384
Loss	13697~16383	2686/16384

Random number range: 0~16383

Fig. 10

Start command		Reel stop command		1 gaming completion command	
1	Internal winning pattern	1	Stop order	1	Prize type
	SB		First stop		SB
	Bell		Second stop		Bell
	Watermelon		Third stop		Watermelon
	Cherry				Cherry
	Replay				Replay
	BB				BB
	RB				RB
	Loss				Loss
3	Gaming status	1	Stop reel	1	Bonus gaming state
	In Common gaming		Left reel		Common gaming 1 in BB
	In RB internal winning		Middle reel		Common gaming 2 in BB
	In BB internal winning		Right reel		Common gaming 3 in BB
	RB in operation				RB Gaming 1
	BB in operation				RB Gaming 2
					RB Gaming 3
					RB completion
					BB completion
5	Selection stop table	2		2	
	Table No.1				
	Table No.2				
	Table No.3				
	Table No.4				
	Table No.5				
	Table No.6				
7	Inlet coin number	8			
	1				
	2				
	3				

Fig. 11

Receipt flag
BR continuance number counter
BR flag
BR evacuation flag
Attraction lottery processing random number

Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

1a	2a	3a
1b	2b	3b
1c	2c	3c

4a	5a	6a
4b	5b	6b
4c	5c	6c

200ms

Fig. 17




Fig. 18




Fig. 19




Fig. 20

1	Transmission source information	1	Transmission source information
2	Game start information	2	Bonus internal winning information
3	—	3	Bonus categories

1	Transmission source information	1	Transmission source information
2	Inlet coin information	2	WIN lamp lighting information
3	Number of inlet	3	ON/OFF

1	Transmission source information	1	Transmission source information
2	Payout coin information	2	Calling information
3	Number of inlet	3	ON/OFF

1	Transmission source information	1	Transmission source information
2	Bonus prize generation information	2	Error information
3	Bonus categories	3	Generation/release

1	Transmission source information		
2	Bonus gaming completion information		
3	Bonus categories		

Fig. 21

Established flag	BR continuance number			
	10 games	50 games	100 games	Loss
Watermelon	0~10	11~13	14~15	16~127
Two cherries	0~6	7~10	—	11~127
Loss	0~14	—	15~24	25~127

Random number range: 0~1

Fig. 22 A

Established flag	Attraction mode ①	Attraction mode ②	Attraction mode ③
BB	0~16	17~64	65~127
RB	0~87	88~105	106~127

Random number range: 0~127

Fig. 22 B

WIN lamp lighting table	Attraction transmission destination				
	A	B	C	D	E
A	0~63	64~109	110~120	121~123	124~127
B	0~37	38~90	91~121	122~125	126~127
C	0~2	3~23	24~88	89~117	118~127
D	0~2	3~12	13~44	45~101	102~127
E	0~2	3~6	7~16	17~56	57~127

Random number range: 0~127

Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39




Fig. 40




Fig. 41




Fig. 42





Fig. 43



THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)